



- 4 REQUIRES VR300-5 (HOSE ADAPTER KIT) TO MATE WITH HOSE
- 3 FLOW RATE: 300 GPM MAX.
- 2 OPERATING TEMPERATURE RANGE: -40°F TO +120°F
- 1 OPERATING PRESSURE: 60 PSI, PROOF PRESSURE: 125 PSI  
BURST PRESSURE: 250 PSI

NOTES: UNLESS OTHERWISE SPECIFIED

THIS DRAWING IS PROTECTED UNDER COPYRIGHT LAW AND IS THE PROPERTY OF ADEL WIGGINS GROUP, TRANSDIGM INC. DATA CONTAINED HEREIN IS PROPRIETARY TO ADEL WIGGINS GROUP, TRANSDIGM INC. THIS DRAWING AND/OR ANY PART OF THE DATA CONTAINED HEREIN MAY NOT BE COPIED, DUPLICATED OR RELEASED FOR MANUFACTURING OR SALE OF EQUIPMENT OUTSIDE OF ADEL WIGGINS GROUP, TRANSDIGM INC. OR AFFILIATES WITHOUT THE WRITTEN CONSENT OF ADEL WIGGINS GROUP, TRANSDIGM INC. REV. 12/85		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: ANGLES ± 2° DECIMALS .XXX ± .03 DECIMALS .XXXX ± .010	DRAWN JNG KWA ENGR S. TRASK WFO DRW D. SIMPSON QUALITY J. R. GRAGG	DATE 12-8-77 REV 12-8-81 REV 12-8-81 REV 12-11-81	 ADEL WIGGINS GROUP LOS ANGELES, CA 90022  <b>NOZZLE</b>
VR300	INTERPRET SPC FLAGS IN ACCORDANCE WITH ADEL WIGGINS GRP 008	ALL FILLETS, CORNERS AND EDGES R.018/.005	APPROVED S. TRASK	SIZE FUGH NO	DWG NO
NEXT ASSY	125 SURFACE FINISH	INTERPRET DWG PER ML-810-180	CUSTOMER OR DWG RSP APPROVAL	D 79326	VR301
				SCALE 1/1	REV E
					SHEET 2